



FLEXKEY[™] KEYTAG

Indala provides a complete product portfolio with the flexsecur technology - The confidence of security between card and reader.

SUPPORTED WITH INNOVATIVE DESIGN AND RESPONSIVE CUSTOMER CARE.





THE INDALA FLEXKEY'S CONTEMPORARY DESIGN ENABLES IT TO BE EASILY ATTACHED TO A KEY, BADGE CLIP, OR BADGE LANYARD.

Built to withstand harsh operating environments, FlexKey's rugged double-sealed construction also allows for customization. By adding a company logo, the FlexKey is ideally suited for vacation resorts, locker rooms, health spas, apartment buildings, club houses, as well as commercial offices where photo IDs are not required.

FlexKey is compatible with the entire FlexPass[™] reader line, allowing easy incorporation into any existing Indala system. The RF-programmable keytag features the high quality and security benefits that you have come to appreciate in the Indala FlexPass credentials, through the use of FlexSecur authentication. With up to 172 user-definable bits, FlexKey permits the encoding of a wide range of data and information.

An ASSA ABLOY Group company

ASSA ABLOY



FLEXKEY[™] KEYTAG

SPECIFICATIONS

1.725" h x 1.197" w x 0.215" t (43.8 mm x 30.4 mm x 5.46 mm)

Weight

0.191 oz (5.4 g)

Typical Maximum Read Range FlexPass Reader Type Read Range 2" (5.08 cm) Slim/Wallswitch 7" (17.78 cm) Mid-Range Long-Range 15" (38.1 cm)

*Range dependant on local installation conditions.

Temperature

-22°F to +149°F (-30°C to +65°C)

Inkjet Marking

Sales Order No. and matching internal ID number on printed strip on the back side

Construction

Outer Shell: Ultrasonic welded polycarbonate Inner Shell: RF core shielded in epoxy

Programming

Factory or field programmable via FlexPass ProxSmith™ Programmer and Toolkit

1.725' POSITION 43.80 mm 1.197" .215" 30.40 mm 5.46 mm

Coding

Wiegand, ABA Track II Magnetic Stripe, others (contact factory), exact facility code and ID number standard, no gaps, no over-runs.

Packaging

100 sequential units per container.

Standard Part Number

FPKEY-SSSS

125 kHz, printed Indala logo on front side, printed strip for inkjet marking on back side.

INDALA'S NEW FLEXKEY PROXIMITY TAG OFFERS:

Compatibility	Works with FlexPass™, ASR-500, and ASR-600 series readers. It can also be used interchangeably with other Indala credentials.
High Security	Utilizes Indala's FlexSecur™ scheme: data encryption, 172 user definable bits, password, and security between card and reader.
Two points of authentication	The reader first authenticates the credential. After validation, the reader passes the credential's information to the host system for authentication. If the reader does not validate the credential, no information is passed on to the host system.
Rugged and durable design able to withstand harsh environments	Double-sealed construction. Inner electronics fully encapsulated in epoxy. Outer body is an ultra-sonic welded, polycarbonate material.
Versatility	The Tag is designed to be attached to a key ring, badge clip, or badge lanyard.
Attractive design and color	Designed to complement the FlexPass Curve and Wave lines.
Customizable	The surface can be customized with company logos.
Expanded credential information	Use the 172 bits to code employee's office location, grade level, department location, or any other credential information that would be pertinent.
Applications	Designed for health spas, locker rooms, gated communities, apartment buildings, vehicle fleet management, vacation resorts, and corporate environments.

WARRANTY

Indala warrants this product against defects in material and workmanship under normal use and service. The warranty period commences with the date of shipment. See complete warranty statement for further details.

Read range stated when readers installed according to instructions. Read range may vary when mounted on metal.

Specifications subject to change without notice. Indala reserves the right to discontinue any product without notice.

Indala and FlexPass are registered trademarks of Indala, an ASSA ABLOY Group company. All other products or service names are the property of their respective trademark owners. © 2003 Indala. All rights reserved. Printed in the U.S.A. flexkeyds 10-2003



6850 B Santa Teresa Blvd. San Jose, California 95119-1205 USA Toll Free: 800-779-8663 (USA only) Tech. Support: 800-646-3252 (USA only) Phone: +1 408 361 4700 Fax: +1 408 361 4701

European Office Wokingham, Berkshire UK Phone: + 44 (0) 1189 121 780 Fax: +44 (0) 1189 121 790

Asia Pacific Office Hong Kong Phone: +852 2587 6008 Fax: +852 8343 7688

Mexico Office León, Gto. México Phone: +52 477 779 7784 Fax: +52 477 779 1493

São Paulo, Brazil Phone: +55 11 5576 6660 Fax: +55 11 5576 6661

Latin America Office Buenos Aires, Argentina Phone: +54 11 4857 1767 Fax: +54 11 4857 3573